

SenHaiX

WWW.SENHAIXUN.COM

DMR
DIGITAL MOBILE RADIO ASSOCIATION

GT-10D

DIGITAL TWO WAY RADIO

-  LED HIDDEN DISPLAY
-  10W OUTPUT
-  BIG BATTERY CAPACITY
-  ENCRYPTION
-  RECORD FUNCTION



General		
Dimension	140x65x45mm (Without Antenna)	
Weight	360g (Includ Battery)	
Operating Voltage	7.4V DC	
Operating Temperature	-20°C~+40°C	
Antenna Impedance	50Ω	
Transmitter		
	Analog	Digital
Frequency Range	400-470MHz	400-470MHz
Channel Capacity	16	16
Output Power	10W (High) 5W (Low)	10W (High) 5W (Low)
Frequency Stability	± 1ppm	± 1ppm
FM Modulation	12.5KHz(11K0F3E) 25KHz(16K0F3)	
4FSK Digital Modulation		12.5KHz(DATA) 7K60FXD 12.5KHz(DATA+VOICE) 7K60FXE
Adjacent Channel Power	≤-60db	≤-60db
Digital Vocoder Type		AMBE+2TM
Digital Agreement		ETSI-TS102 361-1,-2,-3
Audio Response	+1, -3db	+1, -3db
Audio Distortion	≤5%	≤5%
Stray Radiation	-36dbm	-36dbm
Receiver		
	Analog	Digital
Receiving Sensitivity	0.25uV 12dbSINAD	0.25uV BER3%
Adjacent Channel Selectivity	≤60db	≤60db
Audio Response	+1, -3db	+1, -3db
Audio Distortion	≤5%	≤5%
Audio Output Power	1W	1W
Intermodulation	≤-60db	≤-60db

All stated specifications are subject to change without notice or obligation.

Fujian Senhaix Electronic Technology Co., Ltd

Fujian Senhaix Electronic Technology Co., Ltd. reserves the rights to change product designs and specifications without notice. All information has been seriously checked in order to be accurately. Our company does not take any responsibility if there is any consequence because of errors in printing or translation.

Company Address: No.7 Zihua Road, Jiangnan Hi-tech Industrial Zone, Licheng, Quanzhou, Fujian, China.

SenHaix Belongs to legitimate trademark of Quanzhou Senhaixun Electronic Technology Co., Ltd.